



# N-Z90 W

MAXIMISING USERS TO LIMIT



Finger



RFID



WiFi



LAN



USB



Battery (Optional)



Access Control

## Time Attendance and Access Control

### Storage Capacity

Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	2,00,000



### N-Z90 W

"N - Z90 the model for the companies with large number of Users. All the features packed in this sleek & dynamic model."

### Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

### Communication Interface

Communication	WiFi, TCP/IP, RS232/485, USB
---------------	------------------------------

### Biometric

Push Data	YES
4g GPRS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	1GHz
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



WiFi, TCP/IP, RS232/485, USB



Unaffected by High Temperatures 0° ~ 50°

### Audio/Visual

LCD	4.3" TFT Color Screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

### Software

Desktop, Web, Cloud

### Access control

Wiegand input/output	YES
Relay	YES
Support Exit Reader	Wiegand Reader, Push Button, Remote, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

### Power & Environment

Battery	Optional
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	188 x 65 x 150 mm

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.